

## ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

PRODUCT SPECS	
Capacity <i>lbs</i>	70
Cylinder Diameter <i>inch</i>	32.5
Cylinder Depth inch	20.9
Cylinder Volume cu ft	9.9
Net Weight Ibs	1401
Crated Weight <i>lbs</i>	1484
Machine Width inch	41.5
Machine Depth inch	52
Machine Height <i>inch</i>	59.1
Door Opening inch	16.8
Floor to Door inch	23.6
Shipping Dimensions <i>inch</i> WxDxH	42.3 x 52 x 65.2
Washing Speeds <i>rpm</i>	16/21/26/36/42
Spin Speeds rpm	83/335/530/698/937
G-force	3.17/52/130/225/405
Static Force Transmitted <i>lbs</i>	1790
Dynamic Force Transmitted <i>lbs</i>	403
Frequency of Dynamic Force Hz	15.5
Available Voltages / Wire Conductor / Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional)	Amp 208-240/60/3, 3W+G, 10 208/60/3, 3W+G, 60 240/60/3, 3W+G, 60 208-240/60/3, 3W+G, 10
Drain Diameter <i>inch</i>	3
Water Inlets inch	2 @ 3/4
Recommended Water Pressure PSI	30-60
Water Flow gal/min	16
Steam Connection inch	1/2
Steam Pressure (optional) PSI	29-87
Steam Flow (optional) lbs/h	176
Total Power <i>kW</i>	3.0
Electric Heating Power (optional) kW	20.7

<sup>\*</sup> Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.







