

# EH080

## ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

| PRODUCT SPECS                               |                        |
|---|------------------------|
| Capacity <i>lbs</i>                         | 80                     |
| Cylinder Diameter <i>inch</i>               | 32.5                   |
| Cylinder Depth <i>inch</i>                  | 23.5                   |
| Cylinder Volume <i>cu ft</i>                | 11.3                   |
| Net Weight <i>lbs</i>                       | 1499                   |
| Crated Weight <i>lbs</i>                    | 1583                   |
| Machine Width <i>inch</i>                   | 41.5                   |
| Machine Depth <i>inch</i>                   | 52                     |
| Machine Height <i>inch</i>                  | 59.1                   |
| Door Opening <i>inch</i>                    | 16.8                   |
| Floor to Door <i>inch</i>                   | 23.6                   |
| Shipping Dimensions <i>inch</i><br>WxDxH    | 42.3 x 52 x 65.2       |
| Washing Speeds <i>rpm</i>                   | 21/26/36/42            |
| Spin Speeds <i>rpm</i>                      | 83/335/530/698/931     |
| G-force                                     | 3.17/52/130/225/400    |
| Static Force Transmitted <i>lbs</i>         | 1850                   |
| Dynamic Force Transmitted <i>lbs</i>        | 412                    |
| Frequency of Dynamic Force <i>Hz</i>        | 15.5                   |
| Available Voltages / Wire Conductor / Amp   |                        |
| Hot Water (standard)                        | 208-240/60/3, 3W+G, 10 |
| Electric Auxiliary Heat (optional)          | 208/60/3, 3W+G, 60     |
| Electric Auxiliary Heat (optional)          | 240/60/3, 3W+G, 60     |
| Steam Auxiliary Heat (optional)             | 208-240/60/3, 3W+G, 10 |
| Drain Diameter <i>inch</i>                  | 3                      |
| Water Inlets <i>inch</i>                    | 2 @ 3/4                |
| Recommended Water Pressure <i>PSI</i>       | 30-60                  |
| Water Flow <i>gal/min</i>                   | 16                     |
| Steam Connection <i>inch</i>                | 1/2                    |
| Steam Pressure (optional) <i>PSI</i>        | 29-87                  |
| Steam Flow (optional) <i>lbs/h</i>          | 176                    |
| Total Power <i>kW</i>                       | 4.2                    |
| Electric Heating Power (optional) <i>kW</i> | 20.7                   |

\* Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.

